

CLAIM AMENDMENTS

The following list of claims replaces all prior versions and lists of claims.

1. (Currently Amended) A method of measuring the availability of a network element or service, the method comprising the computer-implemented steps of:
determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value; and
storing the second availability value;
wherein determining the second availability value further comprises:
determining a dividend based on the first availability value, the first time value, the second time value, and the first operational state value; and
dividing the dividend by the second time value.
2. (Canceled)
3. (Currently Amended) A method as recited in Claim [[2]]1, wherein determining the dividend further comprises the steps of:
determining a first addend based on the first availability value and the first time value;
determining a second addend based on the first operational state value, the second time value, and the first time value; and
adding the first addend and the second addend.
4. (Original) A method as recited in Claim 3, wherein determining the first addend further comprises multiplying the first availability value and the first time value.
5. (Original) A method as recited in Claim 3, wherein determining the second addend further comprises the steps of:
determining a multiplicand based on the second time value and the first time value;
and

multiplying the multiplicand and the first operational state value.

6. (Original) A method as recited in Claim 5, wherein determining the multiplicand further comprises the step of subtracting the first time value from the second time value.
7. (Original) A method as recited in Claim 1, further comprising the steps of:
determining a third availability value based on the second availability value, the
second time value, a third time value that differs from the second time value,
and a second operational state value; and
storing the third availability value.
8. (Original) A method as recited in Claim 1, wherein determining the second
availability value further comprises the steps of:
detecting a command; and
in response to detecting the command, determining a third availability value based on
the second availability value, the second time value, a third time value that
differs from the second time value, and a second operational state value.
9. (Original) A method as recited in Claim 1, further comprising the steps of:
detecting an event while a current state is a first state that is in a first state cluster;
in response to detecting the event, selecting, based on the current state and a type of
the event, a second state that is in a second state cluster;
determining whether the first state and the second state are in different state clusters;
and
in response to determining that the first state and the second state are in different state
clusters, determining a third availability value based on the second availability
value, the second time value, a third time value that differs from the second
time value, and a second operational state value that differs from the first
operational state value.
10. (Original) A method as recited in Claim 1, further comprising the steps of:

- determining whether the second availability value is less than a lowest recorded availability value; and
if the second availability value is less than the lowest recorded availability value, then storing the second availability value as the lowest recorded availability value.
11. (Original) A method as recited in Claim 1, further comprising the steps of:
comparing the second availability value with the first availability value;
based on the comparing, selecting, from among a plurality of trend indicators, a particular trend indicator; and
storing the particular trend indicator.
12. (Original) A method as recited in Claim 11, wherein selecting the particular trend indicator further comprises the steps of:
selecting a first trend indicator if the first availability value is less than the second availability value;
selecting a second trend indicator if the first availability value is equal to the second availability value; and
selecting a third trend indicator if the first availability value is greater than the second availability value;
wherein the first, second, and third trend indicators differ from each other.
13. (Currently Amended) ~~A method as recited in Claim 1, further comprising the steps of:~~ A method of measuring the availability of a network element or service, the method comprising the computer-implemented steps of:
determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value;
storing the second availability value;
determining a third availability value based on the first availability value, the second availability value, and a weight value; and
storing the third availability value.

14. (Original) A method as recited in Claim 13, wherein determining the third availability value further comprises the steps of:
determining a dividend based on the first availability value, the second availability value, and the weight value;
determining a divisor based on the weight value; and
dividing the dividend by the divisor.
15. (Original) A method as recited in Claim 14, wherein determining the dividend further comprises the steps of:
determining an addend based on the second availability value and the weight value;
and;
adding the addend and the first availability value.
16. (Original) A method as recited in Claim 15, wherein determining the addend further comprises the step of multiplying the second availability value and the weight value.
17. (Original) A method as recited in Claim 13, further comprising the step of:
determining the weight value based on the difference between the first time value and the second time value.
18. (Original) A method as recited in Claim 13, further comprising the step of:
determining the weight value based on a type of event.
19. (Original) A method as recited in Claim 13, further comprising the step of:
determining the weight value based on a type of the network element.
20. (Original) A method of measuring the availability of a network element or service, the method comprising the computer-implemented steps of:
detecting an event while a current state is a first state that is in a first state cluster;
in response to detecting the event, selecting, based on the current state and a type of

- the event, a second state that is in a second state cluster;
determining whether the first state and the second state are in different state clusters;
and
in response to determining that the first state and the second state are in different state clusters, performing the steps of:
multiplying a current availability value and a current time value to produce a first addend;
subtracting the current time value from a new time value to produce a multiplicand;
multiplying the multiplicand and an operational state value to produce a second addend;
adding the first addend and the second addend to produce a dividend;
dividing the dividend by the new time value to produce a new availability value;
setting the current availability value equal to the new availability value; and
setting the current time value equal to the new time value.
21. (Original) A method as recited in Claim 20, wherein the new time value is equal to the amount of time between an initializing of the network element or service and the detecting of the event.
22. (Original) A method as recited in Claim 20, further comprising the step of determining the operational state value based on which particular state cluster among a plurality of state clusters contains the first state.
23. (Original) A method as recited in Claim 20, further comprising the step of setting the current state equal to the second state.
24. (Currently Amended) A computer-readable storage medium carrying one or more sequences of instructions for measuring the availability of a network element or service, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:

- determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value; and
storing the second availability value;
wherein determining the second availability value further comprises:
determining a dividend based on the first availability value, the first time value, the second time value, and the first operational state value; and
dividing the dividend by the second time value.
25. (Canceled)
26. (Currently Amended) A computer-readable storage medium as recited in Claim [[25]]24, wherein determining the dividend further comprises the steps of:
determining a first addend based on the first availability value and the first time value;
determining a second addend based on the first operational state value, the second time value, and the first time value; and
adding the first addend and the second addend.
27. (Currently Amended) A computer-readable storage medium as recited in Claim 26, wherein determining the first addend further comprises multiplying the first availability value and the first time value.
28. (Currently Amended) A computer-readable storage medium as recited in Claim 26, wherein determining the second addend further comprises the steps of:
determining a multiplicand based on the second time value and the first time value;
and
multiplying the multiplicand and the first operational state value.
29. (Currently Amended) A computer-readable storage medium as recited in Claim 28, wherein determining the multiplicand further comprises the step of subtracting the first time value from the second time value.

30. (Currently Amended) A computer-readable storage medium as recited in Claim 24, further comprising instructions for performing the steps of:
determining a third availability value based on the second availability value, the second time value, a third time value that differs from the second time value, and a second operational state value; and
storing the third availability value.
31. (Currently Amended) A computer-readable storage medium as recited in Claim 24, wherein determining the second availability value further comprises the steps of:
detecting a command; and
in response to detecting the command, determining a third availability value based on the second availability value, the second time value, a third time value that differs from the second time value, and a second operational state value.
32. (Currently Amended) A computer-readable storage medium as recited in Claim 24, further comprising instructions for performing the steps of:
detecting an event while a current state is a first state that is in a first state cluster;
in response to detecting the event, selecting, based on the current state and a type of the event, a second state that is in a second state cluster;
determining whether the first state and the second state are in different state clusters;
and
in response to determining that the first state and the second state are in different state clusters, determining a third availability value based on the second availability value, the second time value, a third time value that differs from the second time value, and a second operational state value that differs from the first operational state value.
33. (Currently Amended) A computer-readable storage medium as recited in Claim 24, further comprising instructions for performing the steps of:
determining whether the second availability value is less than a lowest recorded availability value; and

- if the second availability value is less than the lowest recorded availability value, then storing the second availability value as the lowest recorded availability value.
34. (Currently Amended) A computer-readable storage medium as recited in Claim 24, further comprising instructions for performing the steps of:
comparing the second availability value with the first availability value;
based on the comparing, selecting, from among a plurality of trend indicators, a particular trend indicator; and
storing the particular trend indicator.
35. (Currently Amended) A computer-readable storage medium as recited in Claim 34, wherein selecting the particular trend indicator further comprises the steps of:
selecting a first trend indicator if the first availability value is less than the second availability value;
selecting a second trend indicator if the first availability value is equal to the second availability value; and
selecting a third trend indicator if the first availability value is greater than the second availability value;
wherein the first, second, and third trend indicators differ from each other.
36. (Currently Amended) ~~A computer-readable medium as recited in Claim 24, further comprising instructions for performing the steps of:~~ A computer-readable storage medium carrying one or more sequences of instructions for measuring the availability of a network element or service, which instructions, when executed by one or more processors, cause the one or more processors to carry out:
determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value;
storing the second availability value;
determining a third availability value based on the first availability value, the second availability value, and a weight value; and
storing the third availability value.

37. (Currently Amended) A computer-readable storage medium as recited in Claim 36, wherein determining the third availability value further comprises the steps of:
determining a dividend based on the first availability value, the second availability value, and the weight value;
determining a divisor based on the weight value; and
dividing the dividend by the divisor.
38. (Currently Amended) A computer-readable storage medium as recited in Claim 37, wherein determining the dividend further comprises the steps of:
determining an addend based on the second availability value and the weight value;
and;
adding the addend and the first availability value.
39. (Currently Amended) A computer-readable storage medium as recited in Claim 38, wherein determining the addend further comprises the step of multiplying the second availability value and the weight value.
40. (Currently Amended) A computer-readable storage medium as recited in Claim 36, further comprising instructions for performing the step of:
determining the weight value based on the difference between the first time value and the second time value.
41. (Currently Amended) A computer-readable storage medium as recited in Claim 36, further comprising instructions for performing the step of:
determining the weight value based on a type of event.
42. (Currently Amended) A computer-readable storage medium as recited in Claim 36, further comprising instructions for performing the step of:
determining the weight value based on a type of the network element.
43. (Currently Amended) An apparatus for measuring the availability of a network

- element or service, comprising:
means for determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value; and
means for storing the second availability value;
wherein the means for determining the second availability value further comprises:
means for determining a dividend based on the first availability value, the first time value, the second time value, and the first operational state value;
and
means for dividing the dividend by the second time value.
44. (Currently Amended) An apparatus for measuring the availability of a network element or service, comprising:
a network interface that is coupled to a data network for receiving one or more packet flows therefrom;
a processor;
one or more stored sequences of instructions which, when executed by the processor, cause the processor to carry out the steps of:
determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value; and
storing the second availability value;
wherein determining the second availability value further comprises the steps of:
determining a dividend based on the first availability value, the first time value, the second time value, and the first operational state value; and
dividing the dividend by the second time value.
45. (New) An apparatus as recited in Claim 44, wherein the one or more stored sequences of instructions further comprises instructions which, when executed by the processor, cause the processor to carry out:

- determining a third availability value based on the second availability value, the second time value, a third time value that differs from the second time value, and a second operational state value; and
storing the third availability value.
46. (New) An apparatus as recited in Claim 44, wherein determining the second availability value further comprises:
detecting a command; and
in response to detecting the command, determining a third availability value based on the second availability value, the second time value, a third time value that differs from the second time value, and a second operational state value.
47. (New) An apparatus as recited in Claim 44, wherein the one or more stored sequences of instructions further comprises instructions which, when executed by the processor, cause the processor to carry out:
detecting an event while a current state is a first state that is in a first state cluster;
in response to detecting the event, selecting, based on the current state and a type of the event, a second state that is in a second state cluster;
determining whether the first state and the second state are in different state clusters;
and
in response to determining that the first state and the second state are in different state clusters, determining a third availability value based on the second availability value, the second time value, a third time value that differs from the second time value, and a second operational state value that differs from the first operational state value.
48. (New) An apparatus as recited in Claim 44, wherein the one or more stored sequences of instructions further comprises instructions which, when executed by the processor, cause the processor to carry out:
determining whether the second availability value is less than a lowest recorded availability value; and
if the second availability value is less than the lowest recorded availability value, then

storing the second availability value as the lowest recorded availability value.

49. (New) An apparatus as recited in Claim 44, wherein the one or more stored sequences of instructions further comprises instructions which, when executed by the processor, cause the processor to carry out:
comparing the second availability value with the first availability value;
based on the comparing, selecting, from among a plurality of trend indicators, a particular trend indicator; and
storing the particular trend indicator.
50. (New) An apparatus as recited in Claim 44, wherein selecting the particular trend indicator further comprises:
selecting a first trend indicator if the first availability value is less than the second availability value;
selecting a second trend indicator if the first availability value is equal to the second availability value; and
selecting a third trend indicator if the first availability value is greater than the second availability value;
wherein the first, second, and third trend indicators differ from each other.
51. (New) An apparatus for measuring the availability of a network element or service, comprising:
a network interface that is coupled to a data network for receiving one or more packet flows therefrom;
a processor;
one or more stored sequences of instructions which, when executed by the processor, cause the processor to carry out:
determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value;
storing the second availability value;
determining a third availability value based on the first availability value, the

second availability value, and a weight value; and
storing the third availability value.

52. (New) An apparatus for measuring the availability of a network element or service, comprising:
- a network interface that is coupled to a data network for receiving one or more packet flows therefrom;
 - a processor;
 - one or more stored sequences of instructions which, when executed by the processor, cause the processor to carry out:
 - detecting an event while a current state is a first state that is in a first state cluster;
 - in response to detecting the event, selecting, based on the current state and a type of the event, a second state that is in a second state cluster;
 - determining whether the first state and the second state are in different state clusters; and
 - in response to determining that the first state and the second state are in different state clusters, performing:
 - multiplying a current availability value and a current time value to produce a first addend;
 - subtracting the current time value from a new time value to produce a multiplicand;
 - multiplying the multiplicand and an operational state value to produce a second addend;
 - adding the first addend and the second addend to produce a dividend;
 - dividing the dividend by the new time value to produce a new availability value;
 - setting the current availability value equal to the new availability value; and
 - setting the current time value equal to the new time value.

53. (New) An apparatus for measuring the availability of a network element or service, comprising:

- means for detecting an event while a current state is a first state that is in a first state cluster;
- means for selecting, in response to detecting the event, based on the current state and a type of the event, a second state that is in a second state cluster;
- means for determining whether the first state and the second state are in different state clusters;
- means for multiplying a current availability value and a current time value to produce a first addend;
- means for subtracting the current time value from a new time value to produce a multiplicand;
- means for multiplying the multiplicand and an operational state value to produce a second addend;
- means for adding the first addend and the second addend to produce a dividend;
- means for dividing the dividend by the new time value to produce a new availability value;
- means for setting the current availability value equal to the new availability value; and
- means for setting the current time value equal to the new time value.

54. (New) An apparatus for measuring the availability of a network element or service, comprising:

- means for determining a second availability value based on a first availability value, a first time value, a second time value that differs from the first time value, and a first operational state value;
- means for storing the second availability value;
- means for determining a third availability value based on the first availability value, the second availability value, and a weight value; and
- means for storing the third availability value.